



DIAMOND GRIP EXTRA-THICK NITRILE POWDER-FREE GLOVES



MODEL NO: **SSP54L, SSP54XL, SSP56L, SSP56XL, SSP57L, SSP57XL**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



REFER TO INSTRUCTIONS

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. INTRODUCTION

Diamond Grip gloves ideal for repair technicians, mechanics, health and safety work, among other uses. Greater elasticity and durability thanks to extra-thick 10mil construction. Chemical resistant and certified to EN ISO 374-1:2016+A1:2018, EN 374-5:2016 and EN420:2003+A1:2009. Raised textured surface vastly improves grip over regular disposable gloves in both wet and dry conditions. Powder-free for those with relevant dermatological conditions.

Notified Body: 2777

Tested By: SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Co. Meath, D15 F8PH, Ireland

Certificate Number: 2777/22358-02/E02-01

SSP54: Green

SSP56: Orange

SSP57: Black

Sizes: 9-10 (L-XL)

2. SAFETY

- ✓ Always perform a risk assessment before using this product. Other PPE such as safety glasses may be required for the task at hand.
- ✓ This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals.
- ✓ The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is tested also), and relates only to the chemical tested. It can be different if the chemical is used in a mixture.
- ✓ It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation.
- ✓ When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves.
- ✓ Before usage, inspect the gloves for any defect or imperfections.
- ✓ The gloves are offering protection against micro-organisms and comply to the test requirements.
- ✓ The penetration resistance has been assessed under laboratory conditions and related only to the test specimen.
- ✓ Ensure the gloves fit the hands comfortably without slipping or splitting. The gloves should fit snugly around the wrist.
- ✓ After use, wearers should visually inspect the glove and remove any contamination from the outer surface before removing the glove from the hand. Alternatively, carefully peel the glove off the hand so that contaminated glove outer does not touch the skin.

3. PERFORMANCE

EN ISO 374-1:2016+A1:2018 / Type B	Level	EN SIO 374-4:2019 Degradation %
40% Sodium Hydroxide (K)	5	10.0
30% Hydrogen Peroxide (P)	2	36.5
37% Formaldehyde (T)	5	17.5

EN ISO 374-5:2016	Level
Protection against Bacteria and Fungi	Pass
Protection against Viruses	Pass

4. MAINTENANCE

NOTE: THIS GLOVE IS FOR SINGLE USE ONLY - NOT REUSABLE.

4.1. STORAGE

- ✓ Store in a cool, dry place, away from excessive heat (50°C).
- ✓ Opened boxes should be shielded from exposure to direct sun or fluorescent lighting.
- ✓ Transport in original packaging.

4.2. OBSOLESCENCE

- ✓ Life span is 3 years from date of manufacture.

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



sales@sealey.co.uk



www.sealey.co.uk